



Tractor de Arrastre QDD10L

Capacidad 1 Tonelada.

▪ **Batería de Litio para cargas de oportunidad**

■ CARACTERÍSTICAS

QDD10L está diseñado completamente alrededor del concepto de tecnología Li-Ion y está equipado con Batería Li-Ion como estándar.

La tecnología de carga de su Smartphone, ahora en su Tractor de Arrastre.

Cargador a elección.

La aplicación del mando a distancia es por rayos infrarrojos.

El control puede controlar fácilmente el tractor para avanzar y retroceder dentro de un cierto rango.

Puede traccionar carga de 1000 kg en una pendiente ó con una pendiente descendente de 3°.

Adopta neumáticos de 250 mm de diámetro que no son fáciles de patinar. La altura del manubrio se puede ajustar para realizar la operación según su comodidad.



Tractor de Arrastre QDD10L

Distinguishing mark				
1.1	Manufacturer			EP
1.2	Model designation			QDD10L
1.3	Drive unit			Battery
1.4	Operator type			pedestrian
1.5	rated capacity	Q	t	1.0
1.7	Rated drawbar pull	F	N	200
1.9	Wheelbase	y (mm)	mm	320
Weight				
2.1	Service weight□ include battery□		kg	120
2.2	Axle loading, laden driving side/loading side			135/0
2.3	Axle loading, unladen driving side/loading side		kg	95/25
Types,Chassis				
3.1	Tyre type driving wheels/loading wheels			rubber
3.2	Tyre size, driving wheels□ diameter×width□		mm	2x Φ250x85
3.3	Tyre size, loading wheels□ diameter×width□		mm	2x Φ75x32
3.5	Wheels, number drivingr/loading (x=drive wheels)		mm	2x /2
3.6	Track width, front,driving side	b10	mm	428
3.7	Track width,rear,loading side	b11	mm	217
Dimensions				
4.8	standing height	h7	mm	
4.9	Height drawbar in driving position min./max.	h14	mm	965±1040±1130
4.12	Tow coupling height scope	h10	mm	
4.19	Overall length	l1	mm	1200~1260~1290
4.21	Overall width	b1/ b2	mm	520±540±570±600±630±660
4.32	Ground clearance, center of wheelbase	m2	mm	
Performance data				
5.1	Travel speed, laden/ unladen		km/ h	4.5/5
5.5	Drawbar pull, laden/unladen		N	200
5.6	Max. drawbar pull, laden/unladen		N	650
5.7	Gradeability, laden/unladen		%	3/16
5.10	Service brake type			Mechanical
Electric-engine				
6.1	Drive motor rating S2 60 min		kW	0.4
6.3	The maximum allowed size battery		mm	196/165/175
6.4	Battery voltage/nominal capacity K20		V/ Ah	24/20
6.5	Battery weight		kg	5.8
Addition data				
8.1	Type of drive unit			DC
10.5	Steering type			Mechanical
10.7	Sound pressure level at the driver's ear		dB (A)	74
10.8	Towing coupling, type DIN 15170			

If there are improvements of technical parameters or configurations, no further notice will be given.
The diagram shown may contain non-standard configurations.

